



D206NT DC – 6 GHz 2-Way N T-Style Resistive Power Divider

FEATURES

- ❖ Low Insertion Loss
- ❖ Low VSWR
- ❖ Excellent Amplitude & Phase Tracking
- ❖ Mounting Hole Option

SPECIFICATIONS

DC – 6 GHz 2-Way N Connector T-Style Resistive Power Divider	
Model Number	D206NT
Frequency Range	DC – 6 GHz
Insertion Loss	0.40 dB Typ., 0.60 dB Max.
Input VSWR	1.08:1 Typ., 1.15:1 Max.
Output VSWR	1.08:1 Typ., 1.15:1 Max.
Amplitude Balance	0.05 dB rms Typ., 0.10 dB rms Max.
Phase Balance	0.4° rms Typ., 0.8° rms Max.
Power Handling	2 W CW
Connector Type	N Female
Operating Temperature	-55 °C To +85 °C

- Note 1. The standard connector is N female, other connector available on request
 Note 2. The nominal Insertion loss of the resistive power divider is 6 dB
 Note 3. Insertion loss is average actual loss above nominal loss
 Note 4. Amplitude and phase balance are RMS value of all the paths at any frequency
 Note 5. Power handling is under the condition that all outputs are connected to the loads with 1.25:1 or better VSWR

